

Circulation fans



VTC500



VTC400



AIR INLET

Housings and wire screens made from stainless steel, while the impellers are from aluminium. The impeller diameters are 400 mm and 500 mm respectively and deliver 2860 and 5300 m³/h free air. Motor voltage : 220 V (380 V optional for 500 mm fan.) Ideal for stirring stagnant air pockets. VTA for controlled air inlet.

VENTURATEC EXHAUST FANS							
Fan size (CODE)	Description	Dia (mm)	Motor kW	Overall size mm	Noise level dB	Nominal Air flow m ³ /h	Mass kg
VT1400	No louvers, double wire screens (belt drive)	1400	1,5	1530x1530x400	<70	55 800	83
VT1400L	With louvers, single wire screen (belt drive)	1400	1,5	1530x1530x400	<70	55 800	85
VT1400F	No louvers, 1.2m legs, 2.4m chimney (frost fan) (belt drive)	1400	1,5	1530x1530x400	<70	55 800	140
VT1270	No louvers, double wire screens (belt drive)	1250	1,1	1380x1380x400	<70	44 000	73
VT1270L	With louvers, single wire screen (belt drive)	1250	1,1	1380x1380x400	<70	44 000	75
VT1270LS	With louvers, double wire screen (belt drive)	1250	1,1	1380x1380x400	<70	44 000	75
VT1270C	With cone, two wire screens standard (belt drive)	1250	1,1	1380x1380x1300	<64	51000	90
VT1300L	With louvers, single wire screen	1300	0,75	1380x1380x400	<70	40 000	75
VT1000	No louvers, double wire screens (belt drive)	1000	0,75	1100x1100x400	<70	32 500	53
VT1000L	With louvers, single wire screen (belt drive)	1000	0,75	1100x1100x400	<70	32 500	54
VT1000H	Cow fan Wire screens, hanging from roof (belt drive)	1000	0,75	1100x1100x400	<70	32 500	45
VT750	No louvers, double wire screens (direct drive)	750	0,55	820x820x350	<70	22 000	39
VT750L	With louvers, single wire screen (belt drive)	750	0,55	900x900x400	<70	22 000	40
VT750L	With louvers, single wire screen (direct drive)	750	0,55	820x820x400	<70	22 000	40
VT500L	With louvers, single wire screen (direct drive)	500	0,37	620x620x400	<60	5 700	23
VTC500	Two wire screens, ss casing, 220V, 120 W	500	0,12	Ø560x390	<70	5 300	10
VTC400	Two wire screens, ss casing, 220V, 80W	400	0,08	Ø450x310	<70	2 860	8,5
VTA	Air inlet, for opening of 610 x 250 mm			650x355x300			